



Pulsation Dampener (Snubber) Adjustable type

Special Features

- Designed to reduce dampening effect of process fluid
- Working pressure up to 400 kg/cm²
- Working temperature up to 120°C
- All stainless steel construction
- For corrosive media & environment

Application

- This device can increase the service life of pressure instruments in critical conditions found at reciprocating
- **Pumps**
- Hydraulic machines
- Compressors
- Process plants
- Clean air,
- Non crystallized liquids





Specifications


Standard Version


Working Pressure Up to 400 kg/cm² Working Temperature upto 120°C Instrument Connection Refer How to Order Refer How to Order **Process Connection Body Material** AISI 316 SS

Viton

Sealing 'O' Ring (Internal)

Dimensions - Standard Version





A Notes : Drawings are not to scale. All Dimensions are in mm.

Connections	Α	В	øс	Hex. "H" A/F
1/4" (M x F)	48	34	14	22.0
3/8" (M x F)	50	34	16	22.0
½" (M x F)	55	37	18	25.0

How	To Order	Example
Basic	: Model	
Code		SN
Body		
S6 MO	AISI 316 SS (Standard) SL AISI 316L SS S4 AISI 304 SS Monel BR Brass* HC Hastelloy C	XXX
* In ca	ase of wetted parts of Brass, max. pressure shall be 250 kg/cm²	
Conn	ection	
2NM	1.2BF ¼" BSP (M x F) 3BM.3BF 3/8" BSP (M x F) 4BM.4BF ½" BSP (M x F) (Standard) 4MM.4MF M20 x 1.5 (N 1.2NF ¼" NPT (M x F) 3NM.3NF 3/8" NPT (M x F) 4NM.4NF ½" NPT (M x F) (Standard) 1.2NF ¼" BSPT (M x F) 3TM.3TF 3/8" BSPT (M x F) 4TM.4TF ½" BSPT (M x F)	XXX.XXX
Note	: Connections like Metric / UNF / G / R etc can be provided on request.	
Optio	onal Extras	
oxs	: Oxygen Service MTC Material Test Certificates* CNS Conformity as per NACE Standard (except option Code 'CP')#	# XXX
*Mate	body material only. erial test certificates will be provided for wetted parts only with chemical composition testing. For others, please consult fairing Example: SN . XXX . XXX.XXX . XXX	ctory.

For other optional items, please contact factory for delivery and minimum quantity of order.

Note: Specifications and dimensions given in this product catalogue represents the state of engineering at the time of printing. Modifications may take place and materials specified may be replaced by others without prior notice.